

OIL ANALYSIS

SAMPLE PROPERTIES

DISTILLATION

VOLUME FRACTION DISTILLED		TEMP. °C		METHOD		BAROM PRESS kPa	
0.05		89.5		ASTM D-86		101.3	
0.10		108.0		ROOM TEMP °C		INITIAL BOIL PT °C	
0.15		126.0		26.0		58.0	
0.20		146.0		DISTILLATION SUMMARY VOLUME FRACTION 204 °C NAPHTHA 274 °C KEROSENE 0.33 0.13 343 °C LIGHT GAS/OIL RECOVERED 0.13 0.74 RESIDUE DISTILLATION LOSS 0.25 0.01 RELATIVE DENSITY DISTILLATE RESIDUE _____ _____ BASE TYPE CHARACTERIZATION FACTOR			
0.25		167.5					
0.30		190.5					
0.35		213.0					
0.40		249.5					
0.45		268.0					
0.50		294.0					
0.55		323.5					
0.60		347.5					
0.65		352.5					
0.70		372.0					
FBP		378.0					
CRACKED							

VISCOSITY		
TEMP °C	DYNAMIC mPa.s	KINEMATIC mm ² s ⁻¹
30	6.58	7.88
40	4.18	5.04
50	3.30	4.02

REMARKS



CONTAINER IDENTITY

CHEMICAL & GEOLOGICAL LABORATORIES LTD.

EDMONTON FORT ST. JOHN CALGARY

OIL ANALYSIS



LABORATORY NUMBER

C83-19236

LICENSE NUMBER

OPERATOR NAME

CANADA NORTHWEST ENERGY LIMITED

LOCATION

5-20-3-28 W1

WELL NAME

Oakland et al Pierson 5-20-3-28

SITUATION

SITUATION

FIELD OR AREA

POOL OR ZONE

Mississippian

NAME OF SAMPLER

COMPANY

TEST TYPE

NO

TEST RECOVERY

MULTIPLE
RECOVERY

Y N

SAMPLING POINT

AMT & TYPE OF CUSHION

MUD RESISTIVITY

Test Interval (meters)

TYPE OF PRODUCTION

PLUMPING

FLOWING

GAS LIFT

SWAB

PRODUCTION RATES

WATER

m³/d OILm³/d GAS10³-m³/d

Perforations (meters)

SEPARATOR

TREATER

RESERVOIR

SOURCE

GAUGE PRESSURE

SPS

SEPARATOR

TREATER

RESERVOIR

SOURCE

TEMPERATURE °C

DATE SAMPLED (Y-M-D)

DATE RECEIVED (Y-M-D)

DATE REPORTED (Y-M-D)

ANALYST

OTHER INFORMATION

980 - 983

1983-02-02

1983-02-11

D. Barber

SAMPLE PROPERTIES

DISTILLATION

COLOR OF CLEAN OIL

Brown

S & W (VOLUME FRACTION)

WATER

0.30

SEDIMENT

Trace

TOTAL

0.30

VOLUME
FRACTION
DISTILLEDTEMP
°C

I.S.P.

36

0.05

82

0.10

104

0.15

124

0.20

148

0.25

170

0.30

196

0.35

223

0.40

247

0.45

267

0.50

290

0.55

0.60

0.65

0.70

0.75

0.80

0.85

0.90

0.95

1.00

F&P

METHOD

Hempel ASTM (D-285)

BAROM PRESS (kPa/mm Hg)

88.6

ROOM TEMP °C

28.0

DISTILLATION SUMMARY

(VOLUME FRACTION)

300°C

NAPHTHENA

0.305

370°C

RESIDUENE

0.16

380°C

LIGHT GAS OIL

FOUR POINT

°C

USRM

+10

ASTM

CARBON RESIDUE

(MASS FRACTION)

CONRADSON

0.0368

RAMSBOTTOM

RECOVERED

RESIDUE

DISTILLATION
LOSS

VISCOSITY

TEMP
°C

ABSOLUTE mPa.s

KINEMATIC mm²/s

20

12.0

14.2

30

5.68

6.79

40

4.46

5.37

RELATIVE DENSITY

DISTILLATE

RESIDUE

BASE TYPE: Mixed

CRACKED

293

CHARACTERIZATION FACTOR: 12.1

Total Sulfur: 12.6 g/kg

BS & W determined on sample as received. Remainder of analysis determined on sample after cleaning by centrifuging.



CONTAINER IDENTITY

CHEMICAL & GEOLOGICAL LABORATORIES LTD.

EDMONTON FORT ST. JOHN CALGARY

LABORATORY NUMBER
C84-3832

OIL ANALYSIS

LICENCE NUMBER

OPERATOR NAME

A & B RESOURCES LTD.

LOCATION

11-19-3-28 W1

WELL NAME

A & B et al Pierson 11-19-3-28

FIELD OR AREA

Pierson

POOL OR ZONE

Mississippian

NAME OF SAMPLER

K. Shaw

ELEVATIONS
& B (metres) LARD

COMPANY

TEST TYPE

NO

TEST RECOVERY

MULTIPLE
RECOVERY

Y N

SAMPLING POINT

AMT. & TYPE OF CUSHION

MUD RESISTIVITY

Test Interval (metres)

TYPE OF PRODUCTION

PUMPING

FLOWING

GAS LIFT

SWAB

PRODUCTION RATES

Perforations (metres)

WATER

m³/d

OIL

m³/d

GAS

10³ m³/d

SEPARATOR

TREATER

RESERVOIR

SOURCE

GAUGE PRESSURE

kPa

SEPARATOR

TREATER

RESERVOIR

SOURCE

TEMPERATURE °C

DATE SAMPLED (Y-M-D)

1984-01-10

DATE RECEIVED (Y-M-D)

1984-01-19

DATE REPORTED (Y-M-D)

1984-01-24

ANALYST

S. Sargious

OTHER INFORMATION

SAMPLE PROPERTIES

DISTILLATION

COLOR OF CLEAN OIL

Brown

WATER

0.036

BS & W VOLUME FRACTION

SEDIMENT

Trace

TOTAL

0.036

VOLUME
FRACTION
DISTILLEDTEMP
°C

METHOD

DENSITY

RELATIVE

AS RECEIVED

AFTER CLEANING

0.841

ABSOLUTE g/cm³

AS RECEIVED

AFTER CLEANING

840

TOTAL SULFUR

(MASS FRACTION)
0.0087

TOTAL SALT

g/m³

POUR POINT °C

US B M

AST M

CARBON RESIDUE
(MASS FRACTION)

CONRADSON

RAMSBOTTOM

RVP kPa

VISCOSITY

TEMP
°C

ABSOLUTE mPa s

KINEMATIC mm²/s0.05
0.10
0.15
0.20
0.25
0.30
0.35
0.40
0.45
0.50
0.55
0.60
0.65
0.70
0.75
0.80
0.85
0.90
0.95
1.00

kPa

CRACKED

DISTILLATION SUMMARY
(VOLUME FRACTION)200°C
NAPHTHA270°C
KEROSENE350°C
LIGHT GAS OIL

RECOVERED

RESIDUE

DISTILLATION
LOSS

RELATIVE DENSITY

DISTILLATE

RESIDUE

BASE TYPE:

CHARACTERIZATION FACTOR:

Total Sulfur: 8.7 g/kg

BS & W determined on sample as received. Remainder of analysis determined on sample after cleaning by centrifuging.

CONTAINER IDENTITY PLASTIC		LABORATORY NUMBER 86-0201-1126	
OPERATOR NAME AND ADDRESS GEOCRUDE ENERGY INC.-85 PARTNERSHIP			
LICENCE NO. 	WELL NAME 22 CNW PIERSON 04-21-03-28-W1M BTY.		ELEVATIONS METERS
CPA NUMBER 	POOL OR ZONE 	NAME OF SAMPLER J LUKASIEWICH	COMPANY GEOCRUDE
FIELD OR AREA PIERSON		TEST RECOVERY 	
TEST TYPE NO 		MUD RESISTIVITY @ 25° C	
MULTIPLE RECOVERY 		SAMPLING POINT HEADER	
TEST INTERVAL FROM m		TYPE OF PRODUCTION PUMPING <input type="checkbox"/> FLOWING <input type="checkbox"/> GAS LIFT <input type="checkbox"/> SWAB <input type="checkbox"/>	
TO m		PRODUCTION RATES WATER m ³ /d OIL m ³ /d GAS 10 ³ m ³ /d	
PERFORATIONS FROM m		GAUGE PRESSURE - KPa SEPARATOR TREATER AS RECEIVED 	
TO m		TEMPERATURES °C SEPARATOR TREATER AS RECEIVED 	
DATE SAMPLED Y M D H:M 86 07 15		DATE RECEIVED Y M D 86 07 18	
DATE REPORTED Y M D 86 07 25		ANALYST L.G. & D.H.	

SAMPLE PROPERTIES

COLOR OF CLEAN OIL BLACK		
VOLUME FRACTION WATER TR	BS TR	TOTAL BS & W TR
DENSITY OF CLEAN OIL @ 15 °C RELATIVE 0.845 API 36.0 ABSOLUTE 845		
TOTAL SULPHUR MASS FRACTION 0.0115	RVP 	POUR POINT °C ASTM -12

VISCOSITY		
TEMP °C	DYNAMIC mPa s	KINEMATIC mm ² s ⁻¹
30	6.55	7.84
40	4.34	5.24
50	3.44	4.18

REMARKS

DISTILLATION

VOLUME FRACTION DISTILLED	TEMP. °C	METHOD ASTM D-86	BAROM PRESS kPa 101.3																								
0.05	89.5	ROOM TEMP °C 26.0	INITIAL BOIL PT °C 58.0																								
0.10	107.5	<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th colspan="2">DISTILLATION SUMMARY VOLUME FRACTION</th></tr> <tr> <td>204 °C NAPHTHA</td><td>274 °C KEROSENE</td></tr> <tr> <td>0.33</td><td>0.13</td></tr> <tr> <td>343 °C LIGHT GAS/OIL</td><td>RECOVERED</td></tr> <tr> <td>0.16</td><td>0.78</td></tr> <tr> <td>RESIDUE</td><td>DISTILLATION LOSS</td></tr> <tr> <td>0.21</td><td>0.01</td></tr> <tr> <td colspan="2">RELATIVE DENSITY</td></tr> <tr> <td>DISTILLATE</td><td>RESIDUE</td></tr> <tr> <td> </td><td> </td></tr> <tr> <td colspan="2">BASE TYPE</td></tr> <tr> <td colspan="2">CHARACTERIZATION FACTOR</td></tr> </table>		DISTILLATION SUMMARY VOLUME FRACTION		204 °C NAPHTHA	274 °C KEROSENE	0.33	0.13	343 °C LIGHT GAS/OIL	RECOVERED	0.16	0.78	RESIDUE	DISTILLATION LOSS	0.21	0.01	RELATIVE DENSITY		DISTILLATE	RESIDUE			BASE TYPE		CHARACTERIZATION FACTOR	
DISTILLATION SUMMARY VOLUME FRACTION																											
204 °C NAPHTHA	274 °C KEROSENE																										
0.33	0.13																										
343 °C LIGHT GAS/OIL	RECOVERED																										
0.16	0.78																										
RESIDUE	DISTILLATION LOSS																										
0.21	0.01																										
RELATIVE DENSITY																											
DISTILLATE	RESIDUE																										
BASE TYPE																											
CHARACTERIZATION FACTOR																											
0.15	126.5																										
0.20	145.5																										
0.25	165.5																										
0.30	185.5																										
0.35	213.5																										
0.40	253.5																										
0.45	268.0																										
0.50	291.5																										
0.55	318.5																										
0.60	338.5																										
0.65	350.5																										
0.70	366.5																										
0.75	374.0																										
FBP	378.0																										
CRACKED																											

May 31, 1984

Quest Energy Corporation
General Delivery
Malton, Manitoba
R0M 1L0

Attention: Mr. D. Wickstrom

Dear Sir:

Re: Quest Pierson A4-22-3-28 (WFO) - Crude Oil Quality

Enclosed is a copy of the Oil Quality Analysis Report for a sample which you recently submitted, taken from the subject well. The results of this sample confirm the currently assigned quality classification for the Pierson MC3a-B Pool (i.e.: D253).

Also enclosed is an invoice for \$50.00 for analysis charges.

If you have any questions, please contact the undersigned.

Yours sincerely,

Original Signed By
L. R. DUBREUIL

L. R. Dubreuil
Chief Petroleum Engineer
Petroleum Branch

LED/sb
Encs.

**MANIT
BA**

PETROLEUM BRANCH
975 Century Street
Winnipeg, Manitoba
R3H 0W4

Phone No. 522-3281

[illegible]

Prepared by John A. Williams