Environment Act Licence

Manitoba Environment and Workplace Safety and Health



Licence No.	1295
Issue Date	AUGUST 11, 1989

In accordance with the Manitoba Environment Act (C.C.S.M. c. E125) THIS LICENCE IS ISSUED TO:

## K & H CONCRETE (READY-MIX) LTD.; APPLICANT

The following limits, terms and conditions shall be complied with in connection with the continuing operation of a ready-mix concrete plant located 1/8 mile south of the Floodway, Highway 59 South, on Lot 2, Plan 19696, WLTO, SE 1/4 31-9-4 EPM in the Rural Municipality of Ritchot:

- The Applicant shall not cause or permit the emission of particulate matter from any point of emission of the operation in excess of 0.23 grams per dry standard cubic metre calculated at 25° Celsius and 760 millimetres of mercury.
- 2. The Applicant shall not cause or permit visible emissions from any point of emission of the operation that exhibit an opacity equal to or greater than:
  - a) 40 percent at any time;
  - b) 20 percent for a period exceeding 4 minutes in the aggregate in any one hour.
- 3. The Applicant shall limit the emission of particulate matter from the operation to such an extent that airborne particulate matter from any part or process of the operation does not at any time exhibit an opacity in excess of 5 percent past the property line of the operation.

..../2

MG-15492

4

## K & H CONCRETE (READY-MIX) LTD. - Page 2 -

4

- 4. The Applicant shall not cause or permit the emission of sound from the operation which when measured beyond the property line of the operation in a residential area:
  - a) Subject to b), exceeds an hourly equivalent sound level  $L_{eq}(1)$  of:
    - (i) 60 dBA during the daytime hours of 7:00 a.m. to 10:00 p.m., local time;
    - (ii) 50 dBA during the nighttime hours of 10:00 p.m. to 7:00 a.m., local time.
  - b) Where subjective evaluation or measurements indicate the sound has a significant impulsive characteristic or predominant discrete tone(s), exceeds an hourly equivalent sound level of:
    - (i) 55 dBA during the daytime hours of 7:00 a.m. to 10:00 p.m., local time;
    - (ii) 45 dBA during the nighttime hours of 10:00 p.m. to 7:00 a.m., local time.
- 5. The Applicant shall at the request of the Director:
  - a) conduct emission testing for the emissions referred to in Clause 1 of this Licence within 60 days of the Director's request in a manner satisfactory to the Director; and,
  - b) submit a report containing the emission testing data and all other related data to the Director within 90 days after completion of the emission testing.
- 6. Noise level determinations, pursuant to Clause 4 of this Licence shall be based on measurement made as follows:
  - a) beyond the property line of K & H Concrete (Ready-Mix) Ltd.
  - b) excluding any significant interfering sounds from other sources; and,
  - c) in terms of the equivalent continous sound level averaged over a 1-hour period (60 minutes), using a sound level monitoring device which equals or surpasses the requirements of Canadian Standards Association Standard Z 107.1 - 1973 (or the equivalent) for Type 2 sound level meters, operated on the "A-weighting network" and "slow" meter response.

..../3

- K & H CONCRETE (READY-MIX) LTD. - Page 3 -
  - 7. In this Licence, "Lequivalent" or "Leq" means the equivalent, A-weighted sound level, which signifies the intensity (dBA) of the constant or steady sound level that would result in exposure to the same total A-weighted energy as would the specified time varying sound, if the constant sound level persisted over an equal time interval. "Leq(1)" means the equivalent sound level for a 1-hour period.

4

C.B. Orcutt Director Environmental Control Services

File: 3059.0