Figure No. 9a

Tundra Oil And Gas Partnership

TYPICAL OPEN HOLE WATER INJECTION WELL (WIW) DOWNHOLE DIAGRAM

WELL NAME:	Tundra Ewart Unit 2 HZNTL Open Hole WIW				**WELL LICENCE:**	
Prepared by	WRJ	(average depths)		Date:	2012	
Elevations :						
KB [m]		KB to THF [m]			TD [m]	2400.0
GL [m]		CF (m)			PBTD [m]	
Current Perfs:	**Open Hole**			950.0	to	2400.0
Current Perfs:					to	
KOP:	700 m MD		Total Interval		to	
Tubulars	**Size [mm]**	**Wt - Kg/m**	**Grade**	**Landing Depth [mKB]**		
Surface Casing	244.5	48.06	H-40 - ST&C	Surface	to	140.0
Intermed Csg (if run)	177.8	34.23 & 29.76	J-55 - LT&C	Surface	to	950.0
Open Hole Latera	none	none	none	950.0	to	2400.0
Tubing	60.3 or 73.0 - TK-99	6.99 or 9.67	J-55	Surface	to	940.0

Date of Tubing Installation:

Item	Description	K.B.--Tbg. Flg.	Length 0.00	Top @ m KB
	Corrosion Protected ENC Coated Packer (set within 15 m of Intermed Csg shoe)			
	60.3 mm or 73 mm TK-99 Internally Coated Tubing			
	TK-99 Internally Coated Tubing Pup Jt			
	Coated Split Dognut			
	Annular space above injection packer filled with inhibited fresh water			
	Bottom of Tubing mKB			

Rod String :

Date of Rod Installation:

Bottomhole Pump:

Directions: